FRAMES

and EXTERIOR

WOODWORK

by CURTIS



### CURTIS

Frames and Exterior Woodwork



IN buying doors or other woodwork, as in buying any other important commodity, we are all seeking the greatest value per dollar invested. Modern business has demonstrated that this greatest value can be attained when the product is manufactured in quantities. Quantity production, of course, can only be obtained by limiting the output to certain sizes, certain woods and certain patterns, all of which have been adopted as standard after long experience in meeting the needs of homebuilders.

The complete line of Curtis Woodwork is produced on this basis, and therefore represents the maximum value that you can get for your woodwork dollars. Each door shown in this section of the Curtis Catalog No. 500 is made in quantities, ready for immediate shipment, in the sizes and kinds of wood listed, at the two main Curtis producing plants—Curtis Bros. & Co., Clinton, Iowa, and Curtis & Yale Co., Wausau, Wisconsin.

Naturally, in different sections of the country, local demand varies. For that reason, complete stocks of all designs and sizes of doors or other woodwork items are not carried by all Curtis plants and all dealers. You can be assured, however, that any material you select from the Curtis Catalog No. 500, unless specifically noted on the page where the design appears, is stock and is available for immediate shipment from one of the Curtis factories, subject to prior orders. The selection of your woodwork early in the process of home planning and building is, therefore, desirable. If your woodwork dealer does not have in his own stock the particular piece of woodwork you select, he can consult his Curtis Catalog Supplement and tell you from which factory the order can be shipped, how quickly, and the price.

The sizes and kinds of wood listed on each page are those which are made up in large quantities, with resultant lower cost. Obviously, you will get prompt service and guaranteed unvarying quality when you order from these lists. On doors which are "odd" as to size, design or wood, quantity savings cannot, of course, apply.

#### CURTIS WOODWORK IS DISTRIBUTED BY

> Copyright 1927 Curtis Companies Inc

# FRAMES and EXTERIOR WOODWORK by CURTIS



## ARCHITECTURAL Interior and Exterior WOODWORK Standardized



IN BUYING frames or other exterior woodwork, as in buying any other important commodity, we are all seeking the greatest value per dollar invested. Modern business has demonstrated that this greatest value can be attained when the product is manufactured in quantities. Quantity production, of course, can only be obtained by limiting the output to certain sizes, certain woods and certain patterns, all of which have been adopted as standard after long experience in meeting the needs of homebuilders.

Curtis Woodwork is produced on this basis, and therefore represents the maximum value that you can get for your woodwork dollar.

Naturally, in different sections of the country, local demand varies. For that reason, complete stocks of all designs and sizes are not carried by all Curtis plants and all dealers. You can be assured, however, that any material you select from the Curtis Catalog No. 500 is available for immediate shipment from one of the Curtis factories, subject to prior orders. If your woodwork dealer does not have in his own stock the particular piece of woodwork you select, he can consult his Curtis Catalog Supplement and tell you from which factory your order can be shipped, how quickly, and the price.

The sizes listed on each page are those which are made in large quantities, with resultant lower cost. Obviously, you will get prompt service and guaranteed unvarying quality when you order from these lists. On material which is "odd" as to size, design or wood, quantity savings cannot, of course, apply.

#### CURTIS WOODWORK IS DISTRIBUTED BY

> Copyright 1927 Curtis Companies Inc. Clinton, Iowa



Plain Cap—Frame Building (Siding); 2 x 4 Stud Wall; Jambs 5 5 16" overall

W INDOW and door frames have two functions in building. From the practical standpoint they are the structural part of the building which joins windows, doors, screens, storm sash and blinds

into the walls of the house. From the architectural standpoint, well designed frames add greatly to the appearance of a building by defining the good proportions and correct placing of the openings.

A-Window Frame-Square Head. -34" and 11/8" outside Casing in sizes required for all stock sized windows.

WINDOW FRAME—CIRCLE HEAD.—3/4" and 11/8" outside casing stocked in sizes for all circle head stock windows.

B—Door Frame—Square Head.—3/4" and 11/8" outside casing in sizes required for all stock sized exterior doors.

C—CASEMENT SASH FRAME (Swing in).—34" and 118" outside casing in sizes required for all stock sized casement sash.

D—CASEMENT SASH FRAME (Swing out).—34" and 118" outside casing in sizes required for all stock sized casement sash. CASEMENT SASH FRAMES—CIRCLE HEAD.—Both C and D are furnished to accommodate all circle head stock sash.

For information regarding existing stocks, shipping points and prices, consult your Woodwork dealer's Curtis Catalog Supplement.



Molded Cap—Frame Building (Siding); 2 x 4 Stud Wall; Jambs  $5\frac{5}{16}''$  overall

 $T^{\rm HESE}$  frames differ in appearance from the frames on the preceding page due to the molded cap or top member of the frames on this page, as

E—Door Frame—Square Head.—34" and 11/8" outside casing in sizes required for all stock sized exterior doors.

F—Window Frame—Square Head.—34" and 11/8" outside casing in sizes required for all stock sized windows.


Window Frame—Circle Head.—34" and 11/8" outside casing. Stocked in sizes for all circle head stock windows.

distinguished from the plain cap. Frames for other types of building construction—stucco, masonry, brick veneer—are also shown in this catalog.

G—Casement Sash Frame (Swing in).—34" and 11%" outside casing in sizes required for all stock sized casement sash.

H—Casement Sash Frame (Swing out).—34" and 11%" outside casing in sizes required for all stock sized casement sash.

Casement Sash Frames—Circle Head.—Both G and H are furnished to accommodate all circle head stock sash.



Plain Cap-Stucco Molding-Stucco Building; 2 x 4 Stud Wall; Jambs 5 16" overall

 $F^{OR\ 2\ x\ 4}$  stud walls, a stucco molding around siding frames supplies the necessary "key" for stucco. No window or door, without a good frame, can be

I—Window Frame—Square Head.—34" and 1½" outside casing in sizes required for all stock sized windows.

Window Frame—Circle Head.—34" and 1½" outside

casing in sizes for all circle head stock windows.

J—Door Frame—Square Head.—34" and 1/8" outside casing in sizes required for all stock sized exterior doors.

Door Frame—Circle Head.—Such frames are offered to ac-

entirely weather-proof. These frames have many special construction features that keep wind and moisture out, and heat in.


commodate all of the stock sized circle head exterior doors.

-Casement Sash Frame (Swing in)—Square Head.—34" and 11/8" outside casing in sizes for all stock sized casement sash.

-Casement Sash Frame (Swing out)—Square Head.—34" and 11/8" outside casing in sizes for all stock sized casement sash.

Casement Sash Frames—Circle Head.—Both K and L are furnished to accommodate all circle head stock sash.

For information regarding existing stocks, shipping points and prices, consult your Woodwork dealer's Curtis Catalog Supplement.



Brick Veneer Building; 2 x 4 Stud Wall; Jambs 5516" overall. (Illustrated without band mold)

ALL exposed parts of the frames shown in this book are made of White Pine, recognized by those of

M-Door Frame-Square Head.—Furnished in sizes required for all stock sized exterior doors.

Door Frame-Circle Head.-Such frames are offered to accommodate all stock circle head exterior doors.


N-WINDOW FRAME-SQUARE HEAD.-Furnished in sizes required for all stock sized windows. WINDOW FRAME—CIRCLE HEAD.—Stocked in those sizes long experience in the manufacture and use of woodwork to be most satisfactory for outside work.

which will accommodate all circle head stock windows.

O—Casement Sash Frame (Swing out)—Square Head.—Furnished in sizes required for all stock sized casement sash.

P—Casement Sash Frame (Swing in)—Square Head.—Furnished in sizes required for all stock sized casement sash.

Casement Sash Frame—Circle Head.—Both O and P are furnished to accommodate all sizely head seash. furnished to accommodate all circle head stock sash.



Brick Building (Illustrated with Band Mold)


Q-Window Frame-Square Head.—Furnished in sizes required for all stock sized windows.
Window Frame-Circle Head.—Furnished in sizes to accommodate all circle head stock windows.
R-Door Frame-Square Head (No sill).—Furnished in sizes required for all stock sized exterior doors. DOOR FRAME—CIRCLE HEAD (No sill).—Furnished in sizes to

accommodate all circle head stock exterior doors. S-CASEMENT FRAME (Swing in)-SQUARE HEAD.-Furnished in those sizes that are required for all stock sized casement sash.

T—CASEMENT FRAME (Swing out)—SQUARE HEAD.—Furnished in sizes required for all stock sized casement sash.

CASEMENT SASH FRAME—CIRCLE HEAD.—Both S and T are furnished to accompand to all circle head stock sash.

CASEMENT SASH FRAME—CIRCLE HEAD.—Both S and 1 are furnished to accommodate all circle head stock sash. Window and Sash Frames have jambs  $5\frac{5}{16}$ " overall as standard for use in 9" walls. When used in thicker walls, extension jambs are required. Door Frames for 9" walls have jambs  $5\frac{5}{16}$ " wide; for 13" walls,  $7\frac{7}{4}$ " wide.



#### GROUND STRIP

TOMEET the increasing use of narrow door and window trim, brought about by the advent of the "Mediterranean" house, Curtis has developed two methods of trim application.


The detail at the right (above) covers the application of standard trims. "A" shows a cross-section of the jamb, pulley pocket and ground strip to be covered by the trim. The detail in the center (above) covers the application of trim less than  $3\frac{1}{2}$  inches in width. Two methods are shown, (1) lath ground and (2) Curtis ground. Here "A'"

indicates the width of the lath ground.

When a lath ground is used, the wall lath are extended beyond the studs so as to enter the groove in the jamb, thereby extending the plaster across the pocket space and giving an ample nailing surface.

When the Curtis ground strip is used, it provides a smooth back lining, a keyed surface and a rabbet against which the plaster will finish and adds an extra "wind stop" to the frame in addition to providing a superior nailing surface for the trim. Its size is 1" x 3". Furnished in White Pine.

In addition to providing the best method of applying narrow trim, the Curtis ground strip adds an extra "wind stop."




#### MISCELLANEOUS FRAMES

ONE of the characteristic touches of many Colonial houses is the use of half or quarter-circle sash in the gables. The latter are used in pairs. The quarter

and half circle sash frames are made for  $2 \times 4$  stud wall, circle inside. In ordering C-1667, state whether in pairs; if not, which side circle is on.

Design Number C-1665	NAME Half Circle Frame, Set up (34" or 11%" outside casing)	Sash Opening 2'6" x 1' 6" 3'4" x 1'11"	STUD OPENING 2' 9'' x 1'10'' · 3' 7'' x 2' 3''
C-1667	Quarter Circle Frame, Set up (3/4" or 11/8" outside casing)	1'3'' x 1' 6'' 1'8'' x 1'11''	1' 6'' x 1'10'' 1'11'' x 2' 3''
C-1670	Cellar Sash Frames KD— (2" brick mold)	For sash openings up to $3'4'' \times 2'5''$ For frame opening up to $3'7\frac{1}{2}'' \times 2'$	'9''

For information regarding existing stocks, shipping points and prices, consult your Woodwork dealer's Curtis Catalog Supplement.




#### INSIDE DOOR JAMBS

JAMBS must be machined accurately to member with the trim satisfactorily. Jambs C-1676, C-1677 and C-1678 are not used in large quantities,

C-1575—Double acting door jamb. When used as a single acting door jamb, stops are required and must be specified. Sizes up to 3'0" x 7'0", 5\[^3\]\\$" wide or less and \[^3\]\\$" thick. Stops \[^2\]\" x 1\[^3\]\".
C-1676—Single door jambs for transom openings. Give height of transom and width of transom bar. Sizes up to 3'0" x 7'0", 5\[^3\]\\$" wide or less, \[^3\]\" thick. Stops \[^2\]\" x 1\[^3\]\".

hence a slightly greater time is required for delivery than for the general line of Curtis Woodwork. Jambs furnished in White Pine, Yellow Pine, Oak and Birch.

C-1677—Sliding door jamb. In ordering give total width of wall and state whether for single or double doors. Sizes up to 6'0'' x 7'0'', 34'' thick. Stops ½'' x 134''.
C-1678—Double rabbeted jamb. In ordering give thickness of doors. Sizes up to 3'0'' x 7'0'', 53's'' wide or less, 13's'' thick. If transom is required give height of transom and width of transom bar.



#### BAY WINDOWS


 $B^{\rm AY}$  WINDOWS are a practical and attractive feature in almost any interior, and are second only to the front entrance as an element in the exterior treatment of a building. Whether one wishes it or not, bays always attract attention. For that

BAY—CARVER (Abore).—Made up of Windows C-2508 and C-2512; Brackets C-2470; Crown Molding C-4020 and standard frame parts.

reason, it is essential that they be rightly proportioned and well designed. The suggestions given here show just a few of the many ways in which Curtis windows and frames can be used in bays that will greatly increase the charm of the house.

BAY—DOVER (Below).—Made up of Casement Sash C-2708; Brackets C-2468; Crown Molding C-4010 and standard frame parts.

Bay frames are not carried in stock. They show the possibilities of combinations of standard frame parts, windows, sash, brackets and moldings, illustrated in the Curtis catalog.



#### DORMERS AND BAYS

DORMERS and bays that are attractively detailed and judiciously used are a most effective element of the exterior design in any type of architecture. Your architect can combine Curtis sash, windows, casements and frame parts of standard

DORMER—DEERFIELD (Above).—Made up of Casement Sash C-2719, Wing Sash, Crown Mold C-4028 and standard frame parts. Wing sash must be ordered specially as their dimensions vary with pitch of roof.

sizes to form bays and dormers of interest and individuality for your house. Casements or double hung sash can be used in bay frames, as desired. The wing sash of the dormer and the side sash of the bay suggested above are stationary.

BAY—GREENFIELD (Below).—Made up of Casement Sash C-2708, Stationary Sash and Crown Mold C-4010 and standard frame parts. The stationary sash must be ordered specially as their width depends on the projection desired.



THERE is no detail of exterior woodwork which requires more careful design than dormers. They should always be small, and usually of the same material as the house. When properly proportioned, they add interest to an otherwise monotonous ex-

DORMER—PLYMOUTH (Above).—Made up of Window C-2512, a standard 2 x 4 stud wall frame with Mold C-4200 applied to its outside casing. Square edged material is used under the eaves instead of molding.

panse of roof, and afford a desirable means of increasing usable space in the small house. Without building an additional story, rooms under the roof can often be made sufficiently light and airy for use by simply adding a dormer or two.

DORMER—BEDFORD (Below).—Made up of Window C-2512, a standard 2 x 4 stud wall frame with Mold C-4104 applied to its outside casing, and Crown Mold C-4020. Square edged material completes this attractive dormer.

For dormers for the average house it is not necessary to employ special, made-to-order materials. Use Curtis standard parts.




IT IS not enough that the window openings of your house admit light and air. The cheapest windows and frames you can buy may do that. But they could not have the weather-proof construction necessary to make your home a real shelter—such construction as you get in Curtis windows and

DORMER—CHELSEA (Above).—Made up of Window C-2512 in a standard stucco frame with Band Mold C-4008 and Crown Mold C-4032. Square edged material completes this dormer.

frames. Frames that let you "heat all outdoors," or admit rain to spoil walls and draperies, may cost a little less at first than those bearing the Curtis trademark, but they represent poor economy. Frames you purchase from the Curtis Companies will daily prove that they are a wise investment.

DORMER—CHATHAM (Below).—Made up of Window C-2512 in a standard 2 x 4 stud wall frame with Mold C-4202 at the edge of its outside casing and Crown Mold C-4014.

Bay Frames are not carried in stock. They show the possibilities of combinations of standard frame parts, windows, sash, brackets and moldings, illustrated in the Curtis catalog.




FOR the house of English type, dormers are characteristic. A great variety of suitable combinations are made with Curtis sash, frames and exterior moldings in regular stock sizes and designs. Two of these are illustrated above. These show correct architectural detail and pleasing appearance. These

DORMER—DEDHAM (Above).—Made up of Casement Sash C-2706 in stucco frame with Band Mold C-4008 and Crown Mold C-4032. Square edged material completes the dormer.

dormers are appropriate for houses of Tudor or Elizabethan type, the lower example showing half-timber work. By using Curtis sash and frames in standard rather than "odd" sizes, a considerable saving can be made in the cost of building, without sacrifice of attractiveness or wearing qualities.

Dormer—Carters (*Below*).—Made up of Casement Sash C-2708, in stucco frame parts with Band Mold C-4008. Quarter-round C-4202 and square edged material completes the dormer.




ONE of the most common faults of dormer design is too great projection of the roof, giving a top-heavy effect that is far from restful. Small wood parts, narrow cornice, and windows of pleasing proportions indicate correct designing of dormers. The choice between casements and double hung windows

DORMER—WALTHAM (Above).—Made up of Casement Sash C-2706 in standard frame, with the addition of corner boards and square edged material.

is often a matter of personal preference. Above is shown an example of each, used in well-designed dormers. Since Curtis frames can be had for every kind of building construction, there is an unlimited opportunity to secure new and charming interior and exterior effects.

DORMER—THAYER (Below).—Made up of Window C-2512 in standard frame with Crown Mold C-4028. A good example of "individualizing" a house through standard woodwork parts.




FLAT roofed dormers of different sizes can be built using Curtis sash, frames and moldings in stock sizes. These are suitable for many types of houses, either for small attic windows or for lighting upper story rooms. The frames you receive from the Curtis Companies are well made of seasoned White Pine

DORMER—Avon (*Above*).—Made up of Casement Sash C-2804 in standard frame with Crown Mold C-4028. Corner boards and other square edged material complete the dormer.

and are ready for the painter's brush. You may possibly buy frames of lower price, but you are sure to find that more time and material are required to prepare the cheaper grade for finishing and to install them in the building. You can depend upon the Curtis trademark and its guarantee.

Dormer—Hadley (Below).—Made up of Casement Sash C-2706 in standard frame with Crown Mold C-4028. Corner boards and other square edged material complete the dormer.

Bay Frames are not carried in stock. They show the possibilities of combinations of standard frame parts, windows, sash, brackets and moldings, illustrated in the Curtis catalog.




#### LOUVRES

LOUVRES make the house more comfortable by providing ventilation under the roof. The several styles illustrated fill every condition and provide for various treatments of roof-lines. Curtis louvres

are all framed square on the inside to fit between studs. The angle of the slats makes the construction entirely rain-proof. Each louvre has a solid hinged back 7%" thick, and a stationary wire screen.

Design Number	DESCRIPTION	OPENING SIZES
C-1800	Triangular-Give pitch of roo	of
C-1805	and height of frame required Rectangular 0'8" x 2'6"; 0'8'	' x 3'6''; 1'0'' x 3'6''


Design Number	DESCRIPTION	Opening Sizes
C-1810	Rectangular	0'4" x 2'6" and 0'4" x 3' 6"
C-1815	Half Circle	2'6" x 1'6" and 3'4" x 1'11"
C-1820	Quarter Circle	1'3" x 1'6" and 1'8" x 1'11"



#### SHUTTERS


		SHULLE	KS		
Design Number C-1830 C-1831 C-1832 C-1833 C-1834	Description One panel and stations Same as C-1830 exc cut-out design illustrat stituted in panel. In a and heights, top panel	ept that edissub- ll widths	Design Number C-1838 C-1840 C-1842 C-1844		DESCRIPTION Two panel Rolling Slat Stationary Slat Batten
		SIZES APPLYING TO AL	L Designs		
	1'8" x 3'11½" 1½" 2'0" x 4' 7½" 1½" 2'4" x 3'11½" 1½"	2' 7'' x 4' 7½'' 2'10'' x 4' 7½'' 3' 0'' x 3'11½''	11/8"	3'0'' x 4'7½'' 3'4'' x 4'7½'' 3'8'' x 4'7½''	$1\frac{1}{8}''$

For information regarding existing stocks, shipping points and prices, consult your Woodwork dealer's Curtis Catalog Supplement.



Design Number C-2!01	Name Newel	Size 4" x 4" x 4"0" 5" x 5" x 4"0" 6" x 6" x 4"0"	Design Number C-2110	Name Column	Size 4" x 4" x 8'0"; 9'0"; 10'0" 5" x 5" x 8'0"; 9'0"; 10'0" 6" x 6" x 8'0"; 9'0"; 10'0"
C-2102	Newel	8" x 8" x 4'0" 10" x 10" x 4'0"	C-2111	Column	6" x 6" x 6", 8"0"; 8"0" 8" x 8" x 6"0"; 8"0"; 9"0"; 10"0" 10" x 10" x 6"0"; 8"0"; 9"0"; 10"0"
C-2103	Newel	8" x 8" x 4'0" 10" x 10" x 4'0" 12" x 12" x 4'0"	C-2113	Column	12" x 12" x 6'0"; 8'0"; 9'0"; 10'0" 8" x 8" x 6'0"; 8'0"; 9'0" 10" x 10" x 6'0"; 8'0"; 9'0"

The porch cornice should be of the same form as the main cornice, but of smaller proportions.




ON THIS page and the preceding one fir porchwork is shown. On the following pages material is illustrated that is furnished in White Pine. Newels,


posts, balustrade and other details can be of great assistance in the house design if used discriminatingly, and should be studied carefully.

Design Number C-2120	NAME Baluster Stock	SIZE 1½" x 1½" 1½" x 1¾" 1½" x 1½"	Design Number C-2131 C-2133 C-2135	NAME Bottom Rail Top Rail Bottom Rail	Size 158" x 258" 158" x 312" 158" x 312"
C-2125 C-2127 C-2129	Top Rail Bottom Rail Top Rail	15/8" x 15/8" 15/8" x 31/2" 15/8" x 31/2" 15/4" x 25/8"	C-2137 C-2139	Top Rail Bottom Rail	$\begin{array}{c} 25_{8}'' \times 4^{5_{8}''} \\ 1^{5_{8}}'' \times 2^{5_{8}}'' \\ 2^{3_{8}}'' \times 2^{5_{8}}'' \end{array}$

For information regarding existing stocks, shipping points and prices, consult your Woodwork dealer's Curtis Catalog Supplement.



Design	Name	Size	Design	Name	Size
Number	Column	478'' to 4½'' x 7'5'' and 7'9''	Number	Pilaster 17/8" x	4½" x 7'4" and 7'8"
C-2200	(stayed)	534'' to 5'' x 8'0''	C-2204	(built up)	1½" x 5" x 8'0"
C-2202	Column (built up)	6¾" to 5¾" x 80" 7¾" to 6½" x 8'0" 4½" x 4½" x 7'5" and 7'9" 5" x 5" x 8'0" 5¾" x 5¾" x 8'0" 6½" x 6½" x 8'0"	C-2206 C-2208 C-2210 C-2212	Post (built up) Pilaster (built up) Post (built up) Pilaster (built up)	178" x 534" x 8'0" 178" x 612" x 8'0" 512" x 512" x 8'0" 234" x 512" x 8'0" 312" x 312" x 8'0" 153" x 312" x 8'0"




THESE delicate posts and lattices are graceful, but strongly constructed. They afford a wide range of opportunity for creating altogether charming effects in porches, arbors and pergolas, according to your own individual tastes and the conditions.

All Curtis porchwork is made of weather-resisting woods that will take paint well. All joints in these square columns are treated with white lead and oil, making them tight and water-proof. The same practise is followed in the construction of brackets.

Design Number C-2214 C-2216	Name Post (built up) Pilaster (built up)	Size 4" x 4" x 8'0" 5½" x 5½" x 8'0" 2" x 4" x 8'0"
		2¾" x 5½" x 8'0"


Design Number C-2222 C-2224 C-2230	NAME Post (built up) Intermediate Post Lattice Panel	Size 10" x 10" x 8'0" 3½" x 10" x 8'0" 1'4¾" x 7'1¾" x 2" 1'4¾" x 7'5¾" x 2"
------------------------------------------------	---------------------------------------------------------------	------------------------------------------------------------------------------------------



A BALUSTRADE around the porch provides a degree of privacy that is very acceptable in many houses, and is ornamental as well when built of these Curtis balusters and the rails shown on the

opposite page. Fences and gates, as well as balustrades, can be attractively fashioned of the flat balusters shown. Absolute uniformity of pattern is assured in Curtis material.

Design Number C-2250 C-2252	Name Newel Newel	Size 3" x 3" x 2'2" 5½" x 5½" x 3'6"	Design Number C-2264	Name Baluster	Size 1½" x 1½" x 2'0" 1¾" x 1¾" x 2'0"
C-2262 C-2262	Baluster Baluster	25/8" x 25/8" x 2'0" 15/8" x 15/8" x 2'0"	C-2270 C-2272	Baluster Baluster	15%" x 15%" x 2'0" 11%" x 5" x 2'6" 11%" x 5" x 2'6"




HERE are a variety of porch rails to select from.

Matching top and bottom members are shown

in pairs. The function of porch rail makes simple patterns most desirable. Made of White Pine.

Design Number C-2300	NAME Top Rail Cap Sides Mold	SIZE  334" x 2½" 34" x 334" 34" x 134" 52" x 74"	Design Number C-2306	NAME Top Rail Cap Sides Fillet	Size 314" x 234" 34" x 314" 34" x 314" 114" x 114"	C-2316	NAME Bottom Rail Top Rail Bottom Rail Top Rail	Size 158" x 158" 138" x 134" 138" x 2" 238" x 258"
C-2301 C-2302	Mold Fillet Lattice	5%" x 7%" 34" x 1½" 34" x 1¾8" 15%" x 25%"	C-2308 C-2310	Fillet Bottom Rail Top Rail	1½" x 1½" 2" x 2¾" 1½" x 1½"	C-2320 C-2322	Top Rail Bottom Rail Top Rail Bottom Rail	23/8" x 25/8" 34" x 11/2' 15/8" x 25/8" 15/8" x 25/8"


For information regarding existing stocks, shipping points and prices, consult your Woodwork dealer's Curtis Catalog Supplement.



#### BRACKETS AND RAFTER ENDS

Design Number	Name	Width	LENGTH	PROJEC- TION	THICK- NESS	Design Number	Name	Width	LENGTH	PROJEC- TION	THICK- NESS
C-2400	Gable Bracket	t 95/8"	2'5"	2′0″	35/8"	C-2410	Rafter End	$6\frac{3}{4}''$	1'8"	0'916"	15/8"
C-2402	Gable	, 0			, 0	C-2412	Rafter End	$3\frac{5}{8}''$	2'6"	1'1'5"	158"
	Termination	51/9"-71/9"	2'0"	0'915"	5"	C-2414	Rafter End	35/8"	3'0"	1'6"	15/8"
C-2404	Gable	, , , ,		- / -		C-2416	Rafter End	55/8''	3'6"	2'116"	$1\frac{5}{8}''$
	Termination	51/9"-71/9"	1'8"	0'51/5"	5"	C-2418	Rafter End	51/1"	3'6"	1'7"	21/4"
C-2406	Flower Box	, , , , ,		/ =		C-2420	Rafter End	55/8"	3'0"	1′9″	21/4"
	Bracket	51/6"	1'378"	111/5"	3"	C-2422	Rafter End	55/8"	3'6"	1'9"	21/4"
C-2408	Overhang	/ =	, 0	, _		C-2424	Gable Bracket	35/8"	2'5"	2′0″	35/8"
	Bracket	51/2"	0'61/4"	0'514"	51/6"			7 0			- / 3

Curtis rafter ends and exterior ornaments are cleanly cut by specialized machines.



#### BRACKETS

Design Number C-2450	Name Hood Bracket	Drop 11½"	Length 2'05/8"	Projec- tion 1'7"	THICK- NESS 21/4"	Design Number C-2464	Hood Bracket	201101	Length 2'534"	Projection 2'134"	THICK- NESS 3"
C-2452 C-2454 C-2456 C-2458 C-2460	Hood Bracket Hood Bracket Porch Bracket Porch Bracket Hood Bracket Hood Bracket	1'6" 1'9" 1'9" 1'6" 1'8" 3'2"	2'4" 2'1" 10 <sup>3</sup> 4" 0'5 <sup>1</sup> / <sub>2</sub> " 0'7" 3'6"	2'0" 1'9" 1034" 0'5½" 0'7" 3'2" 2'1"	3" 35%" 5½" 35%" 5½" 5½" 5½" Brace 4½"	C-2468 C-2470 C-2472	Day Didente	0'712"		1'6" 1'912" 1'912" 514x514 square 0'572" 0'512"	35 s" 35 s" 41 2" turned 51 2" 35 \cdot "



#### FLOWER BOX C-2490

FLOWER boxes add to the lived-in, well-groomed quality of a home. They are also a means of bringing a touch of pleasant color to a wall surface that might otherwise lack color or interest. Curtis flower boxes are neatly designed and durably made.

Flower Box C-2490 is made in White Pine, lined throughout with 28-gauge galvanized iron.

Overall dimensions of box, 10" x 1'0" x 3'10". Inside, 9½" x 10½" x 3'8½". Brackets C-2406, 5½" x 1'3½" x 3". Projection 11½".

#### SETTLE C-2495

WHERE the style of the house permits their use, a pair of prim settles at the front or garden entrance forms a bit of exterior furnishing that never fails to attract favorable attention. These quaint benches come in pairs, fitted and ready to put up.

Settle C-2495 is made in White Pine, packed flat in pairs, ready for assembly.

Overall dimensions, height 4'3'' maximum width, 4'0''. Depth  $1'6\frac{1}{2}''$ . Depth of seat 1'4''. Height of seat 18''.

A reputation gained through more than 60 years is jealously guarded by continuously making Curtis Woodwork a quality product

#### Curtis Exterior Woodwork Is Weather Resisting

CURTIS frames, exterior woodwork and porchwork—except the items shown on pages 22 and 23, which are fir—are made of seasoned White Pine, an ideal wood for any outside use. White Pine resists warping effectively. It is unusually free from blemishes.

It takes paint well. All of these points are essential in woodwork which is to be exposed to the weather, with its varying conditions of temperature and humidity. White Pine is therefore especially well adapted to making Curtis exterior woodwork.

#### The Value to You of the Curtis Trademark

WHEN you invest in Curtis material, you are buying a known product, signed by the makers. The Curtis trademark is a symbol of pride in a piece of woodwork that is as well designed and as durably made as it is possible to make it with modern methods,

specialized equipment and expert workmanship. You may be able to buy cheaper material than Curtis, but you can be sure of obtaining the through-and-through values of Curtis manufacture only by making sure that your woodwork bears the Curtis trademark—

#### CURTIS

#### Curtis Material Saves Work on the Job

WHEN you receive your Curtis exterior woodwork, it is ready for your painter's brush. It is clean and bright and smooth,

for it is carefully machined and well protected for shipment. It should be primed as soon as it is put in place on the job.

#### A Complete Line of Woodwork

THIS booklet covers only one section of the complete line of Curtis Woodwork. Many other items of finish are required for building

a house. To select these, and to realize their possibilities, consult other sections of this Curtis Catalog No. 500, as follows:

CURTIS INTERIOR DOORS

CURTIS CABINET AND STAIR WORK
CURTIS WINDOWS

CURTIS MOLDINGS AND TRIM

CURTIS ENTRANCES AND EXTERIOR DOORS

#### Where to Buy Curtis Woodwork

TO PURCHASE Curtis Woodwork, go to the woodwork dealer in your own locality, or to your lumber dealer. In most localities east of the Rockies, there is a Curtis dealer who can give you complete information, including prices, shipping points and time of delivery. In larger cities, especially,

there are Curtis dealers who have many items of Curtis Woodwork in their own stock and on display in their display rooms, so that you may see the actual woodwork you are buying. If you do not know a Curtis dealer, write us for the name of the nearest dealer who sells Curtis Woodwork.